

Technical Data Sheet

Hoxton 2 Column Radiator – Standard Radiator Sizes

Product Code	No. of Sections	Radiator Height (mm)	Radiator Length (mm)	Radiator Depth (mm)	Output Δt 50°C (Watts)	Output Δt 50°C (BTU's)
HX46/2/04	4	460	276	110	275	938
HX46/2/05	5	460	337	110	344	1174
HX46/2/06	6	460	398	110	413	1409
HX46/2/07	7	460	459	110	482	1644
HX46/2/08	8	460	520	110	551	1880
HX46/2/09	9	460	581	110	620	2115
HX46/2/10	10	460	642	110	689	2351
HX46/2/11	11	460	702	110	758	2586
HX46/2/12	12	460	763	110	826	2818
HX46/2/13	13	460	824	110	895	3054
HX46/2/14	14	460	885	110	964	3289
HX46/2/15	15	460	946	110	1033	3524
HX46/2/16	16	460	1007	110	1102	3760
HX46/2/17	17	460	1067	110	1171	3995
HX46/2/18	18	460	1128	110	1240	4231
HX46/2/19	19	460	1189	110	1309	4466
HX46/2/20	20	460	1250	110	1377	4698
HX46/2/21	21	460	1311	110	1446	4933
HX46/2/22	22	460	1372	110	1515	5169
HX46/2/23	23	460	1433	110	1584	5404
HX46/2/24	24	460	1493	110	1653	5640
HX46/2/25	25	460	1554	110	1722	5875
HX46/2/26	26	460	1615	110	1791	6111
HX46/2/27	27	460	1676	110	1860	6346
HX46/2/28	28	460	1737	110	1928	6578
HX46/2/29	29	460	1798	110	1997	6813
HX46/2/30	30	460	1859	110	2066	7049
HX66/2/04	4	660	276	110	376	1283
HX66/2/05	5	660	337	110	470	1604
HX66/2/06	6	660	398	110	564	1924
HX66/2/07	7	660	459	110	659	2248
HX66/2/08	8	660	520	110	753	2569
HX66/2/09	9	660	581	110	847	2890
HX66/2/10	10	660	642	110	941	3211
HX66/2/11	11	660	702	110	1035	3531
HX66/2/12	12	660	763	110	1129	3852
HX66/2/13	13	660	824	110	1223	4173
HX66/2/14	14	660	885	110	1317	4493
HX66/2/15	15	660	946	110	1411	4814
HX66/2/16	16	660	1007	110	1505	5135
HX66/2/17	17	660	1067	110	1599	5455
HX66/2/18	18	660	1128	110	1693	5776
HX66/2/19	19	660	1189	110	1788	6100
HX66/2/20	20	660	1250	110	1882	6421
HX66/2/21	21	660	1311	110	1976	6742
HX66/2/22	22	660	1372	110	2070	7062
HX66/2/23	23	660	1433	110	2164	7383
HX66/2/24	24	660	1493	110	2258	7704
HX66/2/25	25	660	1554	110	2352	8025
HX66/2/26	26	660	1615	110	2446	8345

Product Code	No. of Sections	Radiator Height (mm)	Radiator Length (mm)	Radiator Depth (mm)	Output Δt 50°C (Watts)	Output Δt 50°C (BTU's)
HX66/2/27	27	660	1676	110	2540	8666
HX66/2/28	28	660	1737	110	2634	8987
HX66/2/29	29	660	1798	110	2728	9307
HX66/2/30	30	660	1859	110	2822	9628
HX76/2/04	4	760	276	110	430	1467
HX76/2/05	5	760	337	110	538	1836
HX76/2/06	6	760	398	110	645	2201
HX76/2/07	7	760	459	110	753	2569
HX76/2/08	8	760	520	110	860	2934
HX76/2/09	9	760	581	110	968	3303
HX76/2/10	10	760	642	110	1076	3671
HX76/2/11	11	760	702	110	1183	4036
HX76/2/12	12	760	763	110	1291	4405
HX76/2/13	13	760	824	110	1398	4770
HX76/2/14	14	760	885	110	1506	5138
HX76/2/15	15	760	946	110	1613	5503
HX76/2/16	16	760	1007	110	1721	5872
HX76/2/17	17	760	1067	110	1829	6240
HX76/2/18	18	760	1128	110	1936	6605
HX76/2/19	19	760	1189	110	2044	6974
HX76/2/20	20	760	1250	110	2151	7339
HX76/2/21	21	760	1311	110	2259	7707
HX76/2/22	22	760	1372	110	2366	8072
HX76/2/23	23	760	1433	110	2474	8441
HX76/2/24	24	760	1493	110	2581	8806
HX76/2/25	25	760	1554	110	2689	9174
HX76/2/26	26	760	1615	110	2797	9543
HX76/2/27	27	760	1676	110	2904	9908
HX76/2/28	28	760	1737	110	3012	10276
HX76/2/29	29	760	1798	110	3119	10641
HX76/2/30	30	760	1859	110	3227	11010

- All radiators are supplied in a primer finish or you can choose from a wide range of creative colours and paint effects.
- Colour matching service available.
- A hand polished finish is also available.
- Tapping connections can be ½" or ¾" BSP.
- The Hoxton is also available all electric.
- Every radiator has a 10 year manufacturers guarantee.
- We can also supply a stunning range of period style manual and thermostatic radiator valves.

simply radiators